



GENERAL INFORMATION

KC10 removes grease, wax, silicone, adhesives, tar, tree sap, insects and dirt. This is a quick-flashing product designed to speed initial surface prep before sanding and body work. Don't apply more than you can wipe clean before KC10 dries. This product is **ONLY** for use in national rule areas.



APPLICATION

KC10 is to be used over unsanded surfaces and OEM finishes. **DO NOT USE KC10** over polyester fillers, primers, sealers, or during any step of paint application. **SURFACE PREP CLEANER ONLY.** For Low VOC areas, use KC20.

- Ready-For-Use
- Wash surface with mild detergent and water.
- Rinse and dry surface.
- Soak clean cloth with KC10.
- Wipe surface with KC10 and wipe dry with clean, dry cloth before product dries.

NOTE:

- KC10 should not be allowed to dry on surface. If this occurs, reapply KC10 using a clean cloth and wipe dry.



TECHNICAL DATA

FOR USA (National Rule)

RTS Regulatory Data	KC10	
	Ready-For-Use	
	LBS/GAL	g/L
Actual VOC	6.5 Max.	780 Max.
Regulatory VOC (less water & exempt solvents)	6.43 Max.	770 Max.
Density	6 - 8	720 - 960
	Weight %	Volume %
Total Solid Content	0	0
Total Volatile Content	100	100
Water	0	0
Exempt Compound Content	0	0
Category	Surface Cleaner	

FOR REST-OF-WORLD

RTS Regulatory Data	KC10	
	Ready-For-Use	
	LBS/GAL	g/L
VOC	6.5 Max.	780 Max.
Density	6 - 8	720 - 960
	Weight %	Volume %
Total Solid Content	0	0
Total Volatile Content	100	100
Water	0	0
Category	Surface Cleaner	

Note: ROW considered areas outside US/Canada.

T&T TIPS AND TRICKS

- KC10 is used to remove tar, wax and grease prior to sanding. It's recommended to wipe the surface twice, using clean wipes each time. This product is not meant to be used as a final wipe down product prior to painting. Use KC20 for a final wipe down, followed by tack and prime, seal or paint!